

LANDSLIDE DETECTION SYSTEM USING REMOTE SENSED IMAGE CLASSIFICATION

Neela.K
Assistant Professor,IT
Sri Sairam Engineering College
Chennai, India
neela.it@sairam.edu.in

Hirendirran P
Dept of IT
Sri Sairam Engineering College
Chennai, India
sec122it04@sairamtap.edu.in

Mahendran G
Dept of IT
Sri Sairam Engineering College
Chennai, India
sec21it073@sairamtap.edu.in

Abstract—In this work, a novel technique for identifying and predicting landslide using remote sensing and image classification. Landslide pose a serious threat to communities and infrastructure and require careful monitoring. Our system uses machine learning techniques and high-resolution satellite photos to identify key features in the terrain that indicate landslide-prone areas. We classify earthquakes-prone areas using convolutional neural networks (CNN) and spectral analysis. The effectiveness of the system is demonstrated through extensive use of historical landslide data, demonstrating its potential as an early warning system for landslide mitigation and resource allocation.

Keywords— Big learning and multilayer neural networks are similar., performance comparisons, fine-tuning, classification of remote-sensed images, and transfer learning.

I INTRODUCTION

Landslides are one of the biggest threats and seriously threaten human life, infrastructure and the environment. Solving these problems requires an evaluation process that can detect and predict in a timely manner. The combination of remote sensing technology and advanced image classification techniques provides a great way to create optimal ground performance. presents that apply the capabilities of remote sensing images and machine learning techniques to solve terrain detection problems. Integration of satellite and aerial imagery along with powerful classification techniques helps identify and define earthquake-prone areas. This project's inspiration comes from the need to provide effective protection to reduce impact from the ground. Comprehensive coverage and immediate response are not available in most cultures; This underlines the urgent need for new solutions that can provide early warning and prevention assistance. Our planning process aims to clearly identify and predict earthquake-prone areas using high-resolution remote sensing images and cutting-edge image categorisation algorithms. spectral information and spatial features obtained from these images, the system tries to identify the main features that indicate the possibility of an earthquake.

II. LITERATUREREVIEW

Quality Assessments of Deep Learning Models for Remote Perceptual (2022). There is that much Part Evaluation and comparison of frameworks for deep learning Convolutional CNN-FE, or the Neural Network Feature Separator Chapter View photos. Use CNN-FE, or Neural Network Feature Separator and deep fine-tuning In this article, study samples are used as a comparison sample. Deep Learning Algorithm for Analysis of Location Images category. We analyzed study samples of the UCM dataset and Chapter measurement accuracy, precision, recall, f1 score, Detailed study is given in Section algorithm The CNN-FE is a neural network feature extractor. control detection images as well as distribution performance has been improved. Because It's time to use paper to show the model PartProves that deep learning standards are met There arebest results in the UCM dataset.

Using Deep Reinforcement Learning to Identify Anomalies (2022): For many years, The usage of finding anomalies has been utilised to find and identify anomalies in facts. Numerous methods have been created to identify irregularities. But that simplest is the application of machine learning, which although efficient, continues to be limited to large anonymous data. Deep reinforcement learning (RL)-based techniques outperform existing supervised or unsupervised and other unsupervised detection methods. A systematic literature review (SR) is presented in this work. examining the DRL model to analysis vulnerabilities in applications. This SLR aims to analyze the DR framework for non-objective applications, introduce DRL techniques in addition to compare Their work. with other values. Deep Learning for Malaria Parasite Detection and Enumeration at the Point of Care: Malaria in rural and remote areas of tropical countries remains a public health problem. Early diagnosis, timely treatment and effective treatment are the basis for controlling malaria and reducing the number of malaria cases and deaths worldwide, and are also the key to eliminating malaria. Rapid diagnostic tests (RDTs) remain the main method of malaria diagnosis.

Real- Time Tiny Part Defect Detection System in Manufacturing. Instant small defect detection system in production. It proposes a small-scale vulnerability check based on short-term screen testing (SSD) and deep learning. Finally, we combine real-time product search with mean difference-based mechanical object detection algorithm to solve the invisible problem. We use a 0.8cm darning needle as the test item. When the conveyor belt speed reaches a certain speed, system fault detection is at its highest level. 7.67 m/min.5. Implementation of a modified search dehazing algorithm for integrated, quasi-simultaneous radiometer and radar observations. Estimated soil moisture compared to field measurements probes are considered as ground truth. Error statistics and time series results for the reference area are presented here along with the results obtained from them. Returns the total RMSE and unbiased RMSE of the algorithm covering all reference pixels included in the run. In the simplicity of Section the following The radar part of the algorithm does not need a parameter/curve fit or forward model, and the hybrid radar radiation calculation method does not need a data recommendation letter. .

III. HARDWARE TOOLS

A. Satellite or UAV Imaging Systems: Using satellites or Higher-resolution cameras on unmanned aerial vehicles (UAV) or indicators to capture remote sensing images of the target. Examples include satellites such as Landsat, the Sentinel series, or drones with multi-spectral or hyperspectral sensors

B. Communication Equipment: Slope inclinometer, also known as slope indicator, is used to determine the amplitude, speed, direction, depth and type of soil-rock flow movement. This information is often necessary to understand the causes, behavior and treatment of mudslides.

C. C. Module for the Global System for Mobile Communication (GSM): This module is utilised. to send messages also present position to a mobile phone acts using Google Maps in emergency situations. The Internet of Things applications, the module can be linked to the internet. worldwide system for mobile communications 8500/9800/100/190MHz SM module combined with Satellite navigation using GPS technology. Baud rate can be adjusted between 1200-115200. This model is used to send messages And then present position to a mobile phone number in emergency situations. The module can connect for the of Things on the internet. Key features include frequency bands, GPS integration, configurable baud rate, and IoT connectivity. These applications include emergency alerts, location tracking, and IoT devices.

D. The module for the Global Positioning System (GPS): This module contains USART manner of communication 15, which communicates together using serial communication with the processor. Ground, R, T, and Vc are its four pins. The GPS module (EO-MV2) is utilised for navigation.. This model prints out the product by simply checking its position in the world. This sensor provides the best performance even in the harshest environments.

E. Raindrop sensor: The purpose of this sensor module to measure this amount of rainfall. It operates on the resistance concept. It gauges humidity. Where the sensor for rain detects dampness or water falling The Arduino receives a signal from the sensor. The servo motor is activated via Arduino. starting The wipers' motion. The sensor is usable to measure rainfall in farming and for automatic windscreen wiper control while driving.

IV. PROPOSEDWORK

An earthquake is a destructive event that can cause serious material damage, loss of life and financial loss. Effective and timely detection of earthquakes is important to reduce these effects. This study was designed to develop a landslide detection system that uses remote sensing images to accurately identify and monitor earthquake-prone areas. Data collection methods: Satellite images: High resolution satellite images will be obtained from a variety of sources including Sentinel-2, Landsat 8 and commercial providers. Pre-Processing: To improve image quality and consistency, the image will go through preliminary steps such as radio processing, geometric correction, and cloud removal. Feature extraction: Spectral features: Extract the Normalised Difference Vegetation Index (NVI), spectral bands, and indices and other spectral features to describe vegetation and soil features. Terrain Characterization: Integrating a extract slope, aspect, and elevation data is crucial to understanding the impacts of land on the landscape. Image weight vector machines are used for categori sation. and other way to analysis the slow to phone the all the richest way (RF), as well as with convolutional structure (CNN) to accumulate images as terrestrial and non-terrestrial. Training and implementation: Develop a robust training curriculum that includes field and non-field field recordings. Authentication will be done using cross-verification methods and ground truth data to ensure authenticity. Integration and Analysis: GIS Integration: Integrate classified images with geographic information systems (GIS) to analyze spatial patterns and correlations with environmental factors. Risk Mapping: Using modern technology, it should raise the precision and time at land surveying, Finally, contributing when the safer land survey. , a stronger community. This is a step forward in hazard management

V. METHODOLOGY AND TECHNIQUES USED




Figure: Architecture Diagram

1. Data Acquisition and Preprocessing:

Satellite Images: Get the best satellite images covering the target area and capturing various spectral bands (visible light, near infrared, etc.).

Geospatial Data: Collection of extended data such as elevation models, land cover maps, and historical waste data for training and validation purposes.

2. Extraction and Selection:

Spectral Analysis: Analyzing image features in images to identify specific features associated with earthquake-prone areas.

Texture Analysis: Search for texture patterns to identify terrain features associated with land degradation.

Terrain Parameters: Provides terrain features such as slope, aspect, curvature and elevation to define unstable terrain.

3. Image Classification Techniques:

Machine Learning Algorithms: Employ algorithms for supervised learning. (like strange forest models and support vector machines, convolutional network) to classify image pixels into groups representing earthquake-prone areas and stable zones.

Object-Based Image Analysis (OBIA): Leverage OBIA technology to classify image objects based on shape, content, and spectral information for more accurate land cover classification.

4. Model Training and Validation:

Data preparation: Use log data from historical waste data and ground truth data to train classification models.

Validation and evaluation: validate the model's performance applying different metrics (F1 score, recall, accuracy, and precision) on an independent validation dataset to evaluate its performance in landslide assessment.

6. Monitoring and Updating: Regular monitoring: Using a continuous process to upload new images and update the land protection map.

7. Research and Publication:

Survey Research: Conduct field surveys to identify and remediate earthquake-prone areas based on ground truth surveys.

Reporting and Implementation: Using established processes to ensure stakeholders receive timely and reliable sludge risk information for disposal project management.

VI. EXPERIMENTAL RESULTS

The result of the landslide detection on the whole The shown of the together gathered vector machine, spectrum valid way divert, and adjacent segment match are 94.36%, 84.50%, and 86.44%, calculated, whereas the image produced by the best way technique can reach 97.91%.




Figure : Landslide Detection Precision Comparison

VII. KEY FINDINGS

The proposed method shows high accuracy in determining earthquake-prone areas based on spectral, textural and topographic attributes obtained from remote sensing images. The fact that the system not only gives good results in the field of study, but also is widely seen in different regions or regions shows that it can be used in many areas.

VIII PRATICAL IMPLICATION

The system allows early detection and mapping of landslide-prone areas, allowing authorities to take preventive measures, including land use planning, infrastructure development and evacuation planning in high-risk areas. By providing timely information about mudslide areas, emergency responders and local authorities can better prepare for major disasters, allocate resources effectively, and develop response plans to minimize injury and damage. Understanding the process can help urban planners, engineers and policymakers make decisions about infrastructure. It ensures the safety and durability of roads, buildings and other infrastructure by helping prevent construction when there is a substantial threat. The system contributes protection of environment by identifying areas at risk of earthquakes, helping to develop sustainable land management strategies, protecting ecosystems and preventing soil erosion.

IX. CONCLUSION

In summary, the creation and application of field surveys through the main of all the testing distributed photo display at an important priority in disaster management and risk reduction strategies. This research shows the potential of integrating cutting-edge machine learning and image processing techniques with remote sensing to accurately identify and predict landslide-prone areas. The creation and application of demonstrate this system in identifying areas at risk of mudslides using spectral, textural and terrain features obtained from high- resolution satellite images. The performance demonstrated in different fields demonstrates the applicability of the system beyond the specific study area and represents a significant advance in soil research.

X. FUTURE WORKS

Integrating multiple data sources, such as multi-temporal satellite imagery, lidar data, and high-resolution drone imagery, slows down and refines results to increase power and accuracy in detecting subtle changes. Investigate integrated systems that combine and leverage various classification algorithms or models, thus potentially increasing the overall performance and reliability pressure on soil surveys. This makes it time to update the soil conservation map. Using techniques to quantify uncertainty in forecast models and assess the level of risk associated with landslide-prone areas, providing more data and information for decision-making processes

XI. REFERENCE

1. U. Zhid, K. . Yahya, H. . Hussein, M. . Khan, M. Alhaisoni, I. Ashraf, and H. Alshazly, Comput. Intell. Neurosci., sep. 2022
2. B. Yang, S. Hu, Q. Guo, and D. Hong, IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens., june 2022.
3. Z. Zeng, X. Chen, and Z. Song, "MFN: A multi-granularity technique convolutional network for remote sensing scene classification," IEEE Access, , 2021.
4. A. Shbbir, N. Ali, J. Ahmed, B. Zafar, A. Rasheed, M. Sajid, "space and scene photo classification based on transfer July 2021
5. A. . Haida, P. Labert, and C. Aar, 2-D said for rular sget colour classification, IEEE Remote Aug. 2018.
6. C. Deg, , and D. Tao, "Transfer learned network: A anolmy deep joint spectral spatial feature learning model for hyper sensed image classification April 2023
7. Osedyv, Efficiency big featured selected for remote sensing image recognition with fused small learning architectures J. Supercomputer Aug 2023
8. Han, G. Chng, L. Guo, and H. Ren, "Organised detection in optical remote sensing images based on weakly supervised, sep. 2023.
9. J. Hezipah K. Neela, Sushmitha and Anvitha, "Detection and Anazed of Brain Tumors using Proposed Centerfused ways," 2023 International Conference on Inventive Computation Technologies Nepal, 2023.
10. Blessy, K. Neela, a ""A Long Short-Term Memory Model and Two-Dimensional Convolutional Neural Network for Limb Movement Detection," 2023 International Conference on Artificial Intelligence and Knowledge Discovery in Concurrent Engineering, Chennai, India, 2023.
11. C. Geetha, M. Gomathi shankri, A. Jayasri, K. Neela and S. R.Sherly, International Conference on Innovative Computing, Intelligent Communication, and Smart Electrical Systems (ICES), "A New Approach to Recognising Autism Disorder in Learning Scheme," 2022.
12. J. Hepipah, T. D. Subha, K. Neela, Sushmitha and Anvitha, " Finding and Treating Meningioma Brain Tumours with the Help of the Suggested CNN Architecture," 2023 International Conference on Coperation Technologies,
13. K. Neela, J. G, S. Saranya and S. Subramaniam, " Wearable Device Structured Algorithm for IoT and WSN," 2023 5th International Conference on Intelligent Computing and Control Systems (ICICCS), Tiruchy, India, 2023,